



HORIZONTAL LIFELINE

FrogLine Membrane Roofing Surface Mounted Anchors



- Horizontal lifeline equipped with an engineered energy absorbing region to minimise loads on users and structures in the event of a fall.
- Specifically for use with permanent horizontal height safety lifeline systems, to be mounted on the surface of membrane roofing.
- Continuous connection with 8mm stainless steel cable, utilising the Frogline Shuttle System, upto four users per system, two users per span.
- Suits pitches no greater than 25 degrees on a multitude of roof profiles.

STANDARDS

The FrogLine has been rigorously tested and manufactured in accordance with Australia and New Zealand Standard AS/NZS 1891.2, American Standard ANSI Z359.6-2009, European Standards EN 795:2012 and CEN/TS 16415:2013.

WHAT AM I USED FOR?

A height safety system designed to be mounted on the surface of a membrane roof profile. The intermediate anchor limits the lifeline span distances, the end anchor attachment points are designed for the cable to start and terminate at and the corner unit is designed for the cable to run through the corner anchor re-directing it by up to 45-90 degrees.



Intermediate Anchor
STAT.FROGSSQ001



End Anchor
STAT.FROGSSQ002



Corner Anchor
STAT.FROGSSQ003

PRODUCT PARTS	DESCRIPTION	MATERIALS	QTY
FROGLINE INT	FrogLine Base Intermediate	316 Stainless Steel	1
FROGLINE END	FrogLine Base End	316 Stainless Steel	1
FROGLINE CNR	FrogLine Base Corner	316 Stainless Steel	1
BOLT-M16x35mm-SS	Bolt: M16 x 35mm Stainless Steel	316 Stainless Steel	1
ADV-PLATE-SS-295SQ	SurfaceLink Plate 295mmx295mm-MEMBRANE ROOF	316 Stainless Steel	1
WASHER 70od-Plastic	Washer: 70mm O.D.	Black Plastic	2
WASHER 70od-SS	Washer: 70mm O.D.	316 Stainless Steel	1
NUT M16	Nut: M16	316 Stainless Steel	1
TOGGLE001	Toggle Bolt 300mm	Bolt/PVC/Foam	4



DATA SHEET

