

ADVANCE ABSEILING SURFACELINK



Advance SurfaceLink Abseiling Unit (Stainless Steel)

IMPORTANT NOTICE

Size 14-10 x 75mm Roofing Type 17 Screws are supplied but if they don't penetrate the timber by a minimum of 30mm, longer screws need to be used.

COMPONENTS:

PRODUCT CODE	PRODUCT DESCRIPTION	QUANTITY
HSURFAB001.01	Collared Eyebolt: 316 Stainless Steel	1
HSURFAB001.02	Advance SurfaceLink Plate: Stainless Steel	1
HSURFAB001.03	Washers: 70mm O.D. 316 Stainless Steel	1
HSURFAB001.04	Nut: 16mm 316 Stainless Steel	1
HSURFAB001.05	Adhesive Single Sided Foam Tape	2
HSURFAB001.06	Rivets	10
HSURFAB001.07	Size 14-10 75mm Hex Head Screws with Seal	2

Product Code HSURFAB001

- Needs to be secured with 10 8mm Gesipia Rivets, and 2 Hex Head with Seal, Size 14-10 x 75mm Roofing Type 17 Screws.
- Tested to Australian and New Zealand Standard AS/NZS 1891.4.
- For use on metal roof profile where access to timber is difficult.
- Rated at 15kN.
- Suits a multitude of profiles.