



Terms and Conditions



Website



Catalogue

DATA SHEET

CLASSIC SURFACELINK

Abseil Surface Mounted Anchor



- SurfaceLink suits a multitude of roof profiles.
- For use as an **ABSEILING ANCHOR** on metal roof sheeting where access to the structure is difficult.
- Needs to be secured with 8x 8mm Rivets and 2x Hex Head Screws.

STANDARDS

Complies with AS/NZS 1891.4.

IMPORTANT NOTICE: Size 14-10 x 75mm Roofing Type 17 Screws are supplied but if they don't penetrate the timber by a minimum of 30mm, longer screws need to be used.

WHAT AM I USED FOR?

An anchor point designed for use on metal roof sheet profiles where access to timber is difficult. Adjustable design to suit different roof profiles.

COMPLETE UNIT - PRODUCT CODE: HSURFAB001+FIXINGS

Product Parts	Description	Qty	Weight (kg)	Material
EYEBOLT M16x26mm	Collared Eyebolt: M16x26mm	1	0.274	316 Stainless Steel
ADV-PLATE-SS-305-H	Classic SurfaceLink Plate	1	1.083	316 Stainless Steel
WASHER 70od-SS	Washer: 70mm OD	1	0.082	316 Stainless Steel
WASHER 50od-SS	Washer: 50mm OD	1	0.039	316 Stainless Steel
WASHER M16_SPRING	Spring Washer: M16 316SS	1	0.011	316 Stainless Steel
NUT M16	Nut: M16 316 Stainless Steel	1	0.029	316 Stainless Steel
FOAM-TAPE 29 cm	Adhesive single sided tape	2	0.010	Foam
Rivet_8mm(27.7)	Aluminium 8mm Bulbtite Rivets	8	0.056	Aluminium
SCREW 14.10x75mm	Size 14-10 75mm Hex Head Screws	2	0.030	Coated
			1.617	

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



New Zealand Distributor

Total Height Safety Ltd

0508 443 444

Info@TotalHeightSafety.co.nz



For further information and to order our products visit our website.

www.totalheightsafety.co.nz