Catalogue

Safety**Link**®

Innovative

Fall Protection

FASTFIT DAVIT

Temporary Anchor



The SafetyLink FastFit Davit is a Temporary Anchor suitable for use as part of a personal fall protection system. The FastFit Davit is suitable for having one user suspended from the shuttle and a second user connected to either of the secondary attachment points (Mast or Base).

FALL PROTECTION RATING

The FastFit Davit is rated for one user with a maximum weight of 150kg suspended from the shuttle and one user connected to either of the secondary attachment points.

MATERIALS HANDLING

The Davit may be used to lift materials. Davits used for material lifting purposes shall not be used for supporting a user, see manual for maximum loads allowed on Davit Booms.

STANDARDS

The FastFit Davit Temporary Anchor System is compliant with AS/NZS 5532 and EN795.

All safety procedures must comply in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety system.

Boom 1000mm



Mast 1600mm

PRODUCT CODE: DAVIT_KIT16.10						
Product Parts	Description	Qty	Material			
DAVIT_MAST16	1600mm Mast	1	Aluminium/Stainless Steel/Gal Steel			
DAVIT_BOOM10	1000mm Boom	1	Aluminium/Stainless Steel/Gal Steel			

DAVIT BASE COMPONENTS

 DAVIT_BASE01	DAVIT_BASE02	DAVIT_BASE02.01	DAVIT_BASE02.02
Galvanised Steel	Galvanised Steel	Galvanised Steel	Galvanised Steel
		A.	
DAVIT_BASE.CAP	DAVIT_BASE.SLEEVE	DAVIT_BASE05	CON-M16X200-DONUT
Stainless steel, EPDM	PVC	Galvanised Steel	Stainless Steel, Nylon



New Zealand Distributor

Total Height Safety Ltd
0508 443 444 Info@TotalHeightSafety.co.nz

